

# Jäger Plus

HIGH PERFORMANCE  
MONOCRYSTALLINE PERC MODULE



**G2.3**

## RSM156-6-430M-455M

**156 CELL**

Mono PERC Module

**430-455Wp**

Power Output Range

**1500VDC**

Maximum System Voltage

**21.0%**

Maximum Efficiency

### KEY SALIENT FEATURES



Global, Tier 1 bankable brand, with independently certified state-of-the-art automated manufacturing



Industry leading lowest thermal co-efficient of power



Industry leading 12 years product warranty



Excellent low irradiance performance



Excellent PID resistance



Positive tight power tolerance



Dual stage 100% EL Inspection warranting defect-free product



Module Imp binning radically reduces string mismatch losses



Warranted reliability and stringent quality assurances well beyond certified requirements




Certified to withstand severe environmental conditions

- Anti-reflective & anti-soiling surface minimise power loss from dirt and dust
- Severe salt mist, ammonia & blown sand resistance, for seaside, farm and desert environments
- Excellent mechanical load 2400Pa & snow load 5400Pa resistance



### LINEAR PERFORMANCE WARRANTY




12 year Product Warranty / 25 year Linear Power Warranty



★ Please check the valid version of Limited Product Warranty which is officially released by Risen Energy Co., Ltd



## Dimensions of PV Module Unit: mm



### Our Partners:

## ELECTRICAL DATA (STC)

Model Number	RSM156-6-430M	RSM156-6-435M	RSM156-6-440M	RSM156-6-445M	RSM156-6-450M	RSM156-6-455M
Rated Power in Watts-Pmax(Wp)	430	435	440	445	450	455
Open Circuit Voltage-Voc(V)	52.38	52.50	52.62	52.72	52.82	52.92
Short Circuit Current-Isc(A)	10.47	10.57	10.67	10.77	10.87	10.97
Maximum Power Voltage-Vmpp(V)	43.60	43.70	43.80	43.90	44.00	44.10
Maximum Power Current-Impp(A)	9.87	9.97	10.06	10.15	10.24	10.32
Module Efficiency (%) *	19.8	20.1	20.3	20.5	20.7	21.0

STC: Irradiance 1000 W/m<sup>2</sup>, Cell Temperature 25°C, Air Mass AM1.5 according to EN 60904-3.

\* Module Efficiency (%): Round-off to the nearest number

## ELECTRICAL DATA (NMOT)

Model Number	RSM156-6-430M	RSM156-6-435M	RSM156-6-440M	RSM156-6-445M	RSM156-6-450M	RSM156-6-455M
Maximum Power-Pmax (Wp)	321.8	325.5	329.3	332.9	336.6	340.3
Open Circuit Voltage-Voc (V)	48.20	48.30	48.41	48.50	48.59	48.69
Short Circuit Current-Isc (A)	8.59	8.67	8.75	8.83	8.91	9.00
Maximum Power Voltage-Vmpp (V)	39.90	40.09	40.18	40.26	40.33	40.41
Maximum Power Current-Impp (A)	8.06	8.12	8.20	8.27	8.35	8.42

NMOT: Irradiance at 800 W/m<sup>2</sup>, Ambient Temperature 20°C, Wind Speed 1 m/s.

## MECHANICAL DATA

Solar cells	Monocrystalline, 9BB
Cell configuration	156 cells (6×13+6×13)
Module dimensions	2178×996×40mm
Weight	25.5kg
Superstrate	High Transmission, Low Iron, Tempered ARC Glass
Substrate	White Back-sheet
Frame	Anodized Aluminium Alloy type 6063T5, Silver Color
J-Box	Potted, IP68, 1500VDC, 3 Schottky bypass diodes
Cables	4.0mm <sup>2</sup> (12AWG), Positive(+)270mm, Negative(-)270mm
Connector	Risen Twinsel PV-SY02, IP68

## TEMPERATURE & MAXIMUM RATINGS

Nominal Module Operating Temperature (NMOT)	44°C±2°C
Temperature Coefficient of Voc	-0.29%/°C
Temperature Coefficient of Isc	0.05%/°C
Temperature Coefficient of Pmax	-0.37%/°C
Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500VDC
Max Series Fuse Rating	20A
Limiting Reverse Current	20A

## PACKAGING CONFIGURATION

	40ft(HQ)	20ft
Number of modules per container	540	270
Number of modules per pallet	27	27
Number of pallets per container	20	10
Packaging box dimensions (LxWxH) in mm	2205×1130×1130	2205×1130×1130
Box gross weight[kg]	745	745

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.

©2020 Risen Energy. All rights reserved. Specifications included in this datasheet are subject to change without notice.